



PLANTING LEGEND

PROPOSED LAWN – Cynodon Dactylon \ Bermuda Grass \ Hydromuldh \ 2’ width of Sod adjacent to existing walk


TREES		COMMON NAME	SIZE	QTY	NOTES
	Fraxinus texensis	Texas Ash	15 gal	3	Full form with central leader
	Quercus polymorpha	Mexican White Oak	15 gal	1	Full form with central leader
	Quercus macrocarpa	Burr Oak	15 gal	2	Full form with central leader
	Taxodium mucronatum	Montezuma Cypress	15 gal	1	Full form with central leader
	Existing Trees to Remain				

LANDSCAPE NOTES

1. NO TREES ARE TO BE REMOVED UNDER THIS CONTRACT.
2. GRIND EXISTING STUMPS TO 12” BELOW FINISH GRADE AT LOCATIONS INDICATED.
3. LAWN AREAS TO BE PREPARED FOR NEW SOD AS FOLLOWS:
 - PROTECT CRZ OF EXISTING TREES PER TESC PLAN
 - COMPLETE INSTALLATION OF IRRIGATION SYSTEM PRIOR TO TURF INSTALLATION
 - ERADICATE EXISTING GRASS & WEEDS
 - SCARIFY EXISTING SOIL TO 6” DEPTH (OUTSIDE CRZ ONLY)
 - PLACE 2” DEPTH OF COMPOST AND BLEND INTO EXISTING SOIL
 - FINE GRADE
 - PLACE SOD, ROLL WITH WATER-FILLED ROLLER, WATER DEEPLY
4. STAKE TREE LOCATION FOR OWNER APPROVAL PRIOR TO PLANTING
5. MULCH TO CRZ OF EXISTING TREES WITH 2” DEPTH NATIVE HARDWOOD MULCH

EXISTING SITE EQUIPMENT

- EXISTING TRASH COFFIN (REMOVE)
- EXISTING TRASH CAN (GREAT STREETS)
- EXISTING BENCH (REPLACE/RE-INSTALL)
- EXISTING STREET LIGHT
- EXISTING POLE LIGHT
- EXISTING BICYCLE RACK
- EXISTING PARK SIGN
- EXISTING CURFEW SIGN
- EXISTING HISTORIC MARKER
- DRINKING FOUNTAIN (PARTIAL REMNANT)



FOR REVIEW ONLY
NOT FOR CONSTRUCTION