# Walnut Creek Trail System

## • Trail projects:

- N. Walnut Phase I (3.2 miles) \$5,000,000
  - Construction March 2013
- N. Walnut Phase II (1.7 miles) \$3,000,000
  - Grant for construction approved
  - Preliminary Design underway.
- Southern Walnut (7.3 miles) \$8,100,000
  - Construction March 2012
- Total (12.25 miles) \$16,100,000

# Phase I Trail Alignment



### Length 3.2 Miles

# Major Trail Head Plan Layout

### TRAILHEAD DESIGN CHECKLIST

### TRAILHEAD DESIGN CONCEPT

#### Trailheads should serve as:

- I. Connection Node
- be in proximity to other areas with good public access;
  be easily visible at a distance;
- be a gateway into a specific use system;
- allow for future expansion in alternate directions;
- be not in conflict with other public areas and established uses;
- Information Source

   trail map;
- cautions about levels of difficulty for users;
   warnings about flash flood waters and low water crossings;
   locations and distances to other access points and water fountains;
   points of interest:
- hints about responsible trail use;
- 3. Preparation and Recovery Station
- provide enough space to safely mount/dismount out of traffic flow;
   provide shade from sun;
   provide trainking water;
   provide trainking water;
   provide stating and place to wait for others;
   have good lighting and safety





### Design elements supporting the checklist are as follows:

#### I. Connection Node

- circular paved area of 30-40 ft diameter allows for gathering from any direction;
- collection of vertical elements including seating walls, shade structures, information kiosk, and plantings create good visibility from a distance;
   gate posts/pillars demarcate and signify entrance into a specific use system;
- circular paved area allows for future expansion in alternate directions;
   trailheads are located near parking lots or street intersections for easy public access, good visibility, and avoid infringing on other public uses or activities.
- 2. Information Source
- kiosk housing maps, diagrams, and text information;
   compass design in pavement to aid orientation;
   built from materials and plants reflecting or complimenting the landscape and habitat of Walnut Creek.
- Preparation and Recovery Station

   circular paved area of 30-40 ft diameter provides adequate space to safely mount/dismount out of traffic flow;
   shade provided by trees and canopy structure;
   multi-head drinking fountain provides water;
- trees and railings offer places to lean bikes against;
   seating walls/benches offer places to rest and wait for others;
   human-scale street lamps provide lighting and enhance safety.






### Trailhead Design Concept



Walnut Creek Trail

Editional procession Plansing Urban Design BU&RS SMITH SMITH

August 20, 2004




Pedestrian use of the existing footbridge currently is extremely light due to lack of sidewalk connections to desirable destinations. The new bike trail will provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what is now a relatively isolated provide the linkages that are missing and help convert what isolated provide the linkages that are missing and help convert what isolated provide the linkages that are missing and help convert what isolated provide the linkages that are missing and help convert what isolated provide the linkages that are missing and help convert what isolated provid and underutilized asset into an important component of the 3.3-mile trail.

Dismount areas at either end of the 5-ft wide footbridge allow for safe and easy reduction to pedestrian traffic.

The trail widens to 18 ft. at the dismount areas, which are approximately 25-30 ft. in length. The foot bridge is 216 ft long.

The banks of Walnut Creek in this location are quite steep. Installing a The balloc of Walline Creates in una location are quite steep, assuming a coventional low watter crossing here is not a value strategy because the banks would need extensive cutting back within the 100-year flood plain in order to achieve a safe vertical profile. In this area it would be externely difficult to balance cut and fill in the flood plain as is required by Army Corps of Engineer regulatio

Cantilevering a new 14 ft wide bridge on the side of the existing bridge is not considered practical or economical, and likely could not safely achieve full design width.



January 10, 2005


SOUTH BANK DISMOUNT AREA


NORTH BANK DISMOUNT AREA DETAIL

à o

CTB WITH RAILING TO 42" HEIGHT

Urban Design





# Summary

- N. Walnut Phase I (3.2 miles) \$5,000,000
- N. Walnut Phase II (1.7 miles)
   \$3,000,000
- Southern Walnut (7.3 miles)
  \$8,100,000

• Total (12.25 miles) - \$13,100,000