

<u>Table of Contents for 507 W. 23rd Street Tree Permit</u> <u>Heritage Tree Variance Package</u>

The variance package is organized as follows:

- 1. Cover Sheet
- 2. Staff Memorandum
- 3. Staff Findings of Fact
- 4. Exhibits
- 5. Draft Copy of Environmental Board Motion
- 6. Applicant Memorandum and Documentation





ITEM FOR PLANNING COMMISSION AGENDA

BOARD MEETING

DATE REQUESTED:

March 26, 2013

ADDRESS

507 W. 23rd Street

OF PROPERTY:

TREE PERMIT #:

10884861

NAME OF APPLICANT:

Mike McHone

1904 Guadalupe St. Austin, TX 78713 512-481-9111

CITY ARBORIST

Keith Mars, 974-2755

STAFF:

keith.mars@austintexas.gov

ORDINANCE:

Heritage Tree Ordinance (LDC 25-8-641)

REQUEST:

The applicant is requesting to remove a heritage tree with a stem

greater than 30" in diameter.

STAFF

RECOMMENDATION:

The request to remove the 31" Pecan meets the City

Arborist approval criteria set forth in LDC 25-8-624(A), thus the variance is recommended if transplanting is not a viable option.



MEMORANDUM

TO:

Dave Anderson, Chair

Members of the Planning Commission

FROM:

Keith Mars, City Arborist Program

Planning and Development Review

DATE:

March 26, 2013

SUBJECT:

507 W. 23rd Street Heritage Tree Removal

REQUEST: The applicant is requesting to remove a heritage tree with a stem greater

than 30 inches as allowed under LDC 25-8-643

Area Description

The subject property is comprised of three lots located at 507 W. 23rd Street (Exhibit 1). The zoning for one lot is GO-CO-H-NP and the other two are GO-NP. The three lots are located in the University Neighborhood Overlay District (UNO) (Exhibit 2). The zoning allows for 175' building height, no FAR requirements, and 100% impervious cover. The desired use is an apartment building with structured parking. The property is located in the Shoal Creek Watershed and is subject to urban watershed regulations.

Tree Evaluation

Measurements

The subject tree is a 31.0 inch diameter at breast height (dbh) Pecan (Carya illinoensis). The tree height is 60 feet and the canopy spread is 62 feet (Exhibit 3).

Canopy Conditions

The canopy architecture displays minor asymmetry. Storm damage is evident by the presence of broken stems in the canopy (Exhibit 4). Minor cavities, wounds, and previous stem failures are apparent (Exhibit 5).

A major stem (20-24") wound occurs ~6' above grade (Exhibit 6). Callousing of the wound has occurred and minimal decay detected.

Root System

Root flare is apparent at grade. No defects are apparent. Critical root zone conditions are characterized by a 6" wall abutting the root flare, asphalt parking, turfgrass, and a building structure (Exhibit 7). The depth of the wall is unknown. Surface and subsurface conditions in the critical root zone are poor due to compaction and impervious cover.

Dverall Condition

The biological and physiology condition of the tree appear sound. The structural condition of the tree is sound though defects of concern (e.g. stem wound, storm damage in canopy) are present. Additional details came be found in the City Arborist tree assessment (Exhibit 8).

Variance Request

The variance request is to allow removal of a heritage tree with one stem greater than 30 inches as allowed under LDC 25-8-643.

Recommendations

Transplanting options should be exhausted prior to considering removal. Tree condition, suitable transplant location, and logistics should be considered. If transplanting is not feasible, then retaining the tree onsite in the current location does prevent reasonable use of the property (Exhibit 9). The variance request meets approval criteria for the City Arborist per LDC 25-8-624(A).

Mitigation

Opportunities to mitigate onsite are not available. Possible mitigation opportunities include: (1) mitigation monies into the Urban Forest Replenishment Fund at 300 percent mitigation (\$18,600), (2) 93.0 inches of native trees planted on public property in the Shoal Creek Watershed, or (3) \$18,600 worth of tree care for public trees in the Shoal Creek Watershed.

If you need further details, please contact me at 974-2755 or keith,mars@austintexas.gov.

Keith Mars, Environmental Program Coordinator

Planning and Development Review Department

Michael Embesi, City Arborist

Planning and Development Review Department

George Adams, Assistant Director

Planning and Development Review Department





City Arborist Planning and Development Review Department Staff Recommendations Concerning Heritage Tree Variances

Application Address: 507 W. 23rd Street

Size and Species of Tree(s): 31.0" Pecan (Carya illinoensis)

Reason for Request: The applicant is requesting to remove a heritage tree with a stem

greater than 30 inches as allowed under LDC 25-8-643

Section 1 - Approval Criteria

1) The requirement for which a variance is requested prevents a reasonable access to the property.

No.

- 2) The requirement for which a variance is requested prevents a reasonable use of the property. If transplanting the subject tree is not feasible, then, yes, the tree prevents reasonable use of the property. Please see Exhibit 9 for the reasonable use determination rationale.
- The tree presents an imminent hazard to life or property and the hazard cannot be reasonably mitigated without removing the tree.
 No.
- 4) Is the tree dead?

No.

5) Is the tree diseased? If so, is restoration to a sound condition practicable or can the disease by transmitted?

No.

- 6) For a tree located on public property or a public street or easement, the requirement for which a variance is requested prevents:
 - a) the opening of necessary vehicular traffic lanes in a street or ally, or
 - b) the construction of utility or drainage facilities that may not feasibly be rerouted.

NA.

7) The applicant has applied for and been denied a variance, waiver, exemption, modification, or alternative compliance from another City Code provision which would eliminate the need to remove the heritage tree, as required in Section 25-8-646 (*Variance Prerequisite*).

No.

8) Removal of the heritage tree is not based on a condition caused by the method chosen by the applicant to develop the property, unless removal of the heritage tree will result in a design

that will allow for the maximum provision of ecological service and historic and cultural value from the trees preserved on the site.

Nσ:

01%

Name:

Keith Mars, Environmental Program Coordinator

City Arborist Program


Planning and Development Review Department

Signature:


Kuth- //-

Date:

2/26/13









The City Arborist Program

Tree Preservation and Replenishment



The City Arborist Program

Tree Preservation and Replenishment


Exhibit 3




The City Arborist Program

Tree Preservation and Replenishment

Exhibit 4



Clay



The City Arborist Program.

Tree Preservation and Replenishment

Exhibit 5







Tree Preservation and Replenishment

Critical Root Zone



TREE EVALUATION



Property address: 507 W. 23 ¹²
Date: 2/20/13
Evaluator: Keith Mais
SIGNATURE: Plut 9m
ISA/ASCA Certification #:
is a second continuent on the second continuent of the second continuent on the second continuent of the second continuent on the second continuen
1. TREE CHARACTERISTICS DBH of each trunk: 3' Common & Latin name: 600
2. TREE HEALTH Foliage color: normal / chlorotic / necrotic Epicormics: Y/N Foliage density: normal / sparse Leaf size: normal / abnormal Annual shoot growth: inches Twig dieback: Y/N Callus development: Y/N If so, is callusing: excellent / average / fair / poor Vigor class: excellent / average / fair / poor Major pests/diseases: Nore observed it are evidence.
3. SITE CONDITIONS Site character: residence / commercial / industrial / park / open space / natural / other (see below) Landscape type: parkway / raised bed / container / open / other (see below) Irrigation: none / adequate / inadequate / excessive / trunk wetted Dripline paved: 0% 10-25% 25-50% 50-75% 75-100% Dripline w/ fill soil: 0% 10-25% 25-50% 50-75% 75-100% Dripline grade lowered: 0% 10-25% 25-50% 50-75% 75-100% Dripline grade raised: 0% 10-25% 25-50% 50-75% 75-100% Soil problems: drainage / shallow / compacted / small volume / other (see below) Obstructions: lights / signage / line of sight / view / overhead lines / traffic / other (see below) Wind (tree position): single tree / below canopy / above canopy / recently exposed / canopy edge
Other:

4. TREE DEFECTS - IDENTIFY ALL AREAS AND SEVERITY THAT APPLY TO EACH DEFECT DEFECT DEFECT **DEFECT TYPE** NOTES AREA **SEVERITY LEGEND** Poor toper? Codominants forks angle Multiple attachments 5 T - Trunk(s) Included bark R - Root Flare Excessive end L - Latera! Roots weight S-Scaffolds Cracks/splits B - Branches Hangers SEVERITY Girdling S - Severe Wounds M5 M-ModerateDecay L - Low Cavity Conks/Mushrooms Bleeding Loose/cracked bark Nesting hole/bee hive Deadwood/stubs Borers/termites/ants Cankers/galls Previous failure L. M 7. OTHER FEATURES **Lean:** Ø degrees from vertical Soil heaving: Y (N) natural or unnatural Decay in plane of lean: Y / 🕦 Roots exposed: Y /(N) Soil cracking: Y / N Compounding factors: 6" wall abother out f Lean severity: S / M / L Suspect root rot: Y / N Mushroom/conk present: Y / N ID: Exposed roots: S / M / L Undermined: S / M / L **Root pruned:** feet from trunk Root area affected: _____% Buttress wounded: Y / N Restricted root area: (S / M)/ L Potential for root failure: S / M / (L)6. TARGET AND ABATEMENT building / (parking / traffic / pedestrian / recreation / landscape / hardscape Use under tree: Occupancy: occasional use / medium, intermittent use / frequent use Can target be moved: Y /(N) **RISK ABATEMENT** Action: prune remove / other Comments:

7. COMMENTS OR OTHER RISK FACTORS





City Arborist Reasonable Use Determination: Criteria and Application to the Subject Property

1. Has the applicant applied for and been denied a variance, waiver, exemption, modification or alternative compliance from another city code provision which would eliminate the need to remove the heritage tree?

Due to the location of the tree it does not appear a variance, waiver, exemption, modification or alternative compliance could be sought that would preserve the tree.

2. Is the removal of the heritage tree based on a condition caused by the method chosen by the applicant to develop the property, and if so, will removal of the heritage tree result in a design that will allow for the maximum provision of ecological service, historic, and cultural value of the trees on the site?

Given the central location of the tree, removal does not appear to be based on the method of development chosen.

3. Is this the minimum change necessary?

Yes. No other variances are being sought at this time.

4. What is the zoning and allowable impervious cover for the property? Does intensity of development or size of the lot contribute to reasonable use?

This property is within the UNO district and 100 percent impervious cover is allowed. Yes, the intensity of development contributes to the determination of reasonable use.

5. Is the application to derive reasonable use a result of the actions by the applicant in subdividing the property or adjusting boundary lines (i.e. is this issue self imposed)?

No. The property has not recently been subdivided.

*This document was created by the City Arborist to assist in determining whether a tree proposed for removal prevents a reasonable use of the property. This is not an official or legally binding document, and the considerations used by the City Arborist are subject to change.

6. Does the proposal mitigate the removal to the maximum extent possible?



Staff has provided mitigation options per the Environmental Criteria Manual.

7. Is there a history of non-compliance with the site?

AMANDA records do not indicate a history of non-compliance.

<u>Conclusion:</u> The tree prevents a reasonable use of the property. The City Arborist recommends granting the variance to allow removal of the tree, once mitigation conditions are established and either satisfied or fiscal security posted to ensure performance of the mitigation conditions.

^{*}This document was created by the City Arborist to assist in determining whether a tree proposed for removal prevents a reasonable use of the property. This is not an official or legally binding document, and the considerations used by the City Arborist are subject to change.





ENVIRONMENTAL BOARD MOTION 030613 5c

Date:

March 06, 2013

Subject:

507 W. 23rd Street Tree Permit No 1088486

Motioned By:

Robin Gary

Seconded By: Marisa Perales

Recommendation

The Environmental Board recommends disapproval of the tree variances for 507 W. 23rd Street Tree Permit No 1088486

Rationale:

No site plan accompanies the tree variance request. The Environmental Board is unable to tell whether design consideration have been exhausted. Tree could possibly be preserved or transplanted, but the Board can't tell because no site plant has been proposed.

Vote

4-2-0-1

For:

Gary, Maxwell, Perales, and Walker

Against:

Anderson, and Schissler

Abstain:

Absent: Neely

Approved By:

Dr. Mary Gay Maxwell, Chair

Mike McHone Real Estate

Keith Mars, Heritage Tree Review City of Austin 505 Barton Springs Rd. Austin, TX 78704

February 5, 2013



Re: Heritage Tree Review 507 W. 23rd Street

Dear Mr. Mars;

This memo is to explain the request for the removal of a large pecan tree which is located along the rear of the lot approximately midway into the lot. The lot is part of a three lot site and this tree is in the middle of the site. (survey attached)

This three lot site is located in the University Neighborhood Overlay District (UNO). This special redevelopment district was created in 2004 as part of the adopted Combined Central Austin Neighborhood Plan. The goal of UNO is to create a high density, pedestrian oriented student housing district. The UNO district also serves to reduce the conflicts between student housing in the single family neighborhoods adjacent to the University of Texas and the single family home owners. The City encourages high density redevelopment provided the redevelopment provides buildings that meet community goals set forth in the UNO district requirements. These include affordable housing (S.M.A.R.T), green building, enhanced streetscapes, and design requirements (see attached design requirements)

This site is located in the highest density sub-district of UNO (175 ft). Buildings in UNO are required to build to the property lines, to have the street frontage occupied by active uses, and parking is required to be away from the street and leased separately from the housing unit. Most projects have constructed below grade parking garages with the occupied space above. (see UNO District map) The pecan tree (#6535) is located such that it prohibits the construction of a below grade parking garage. The University Cooperative Society (Coop Book Store) owns the property and needs to sell it. Potential developers will not purchase the property with a heritage tree in the middle of the site. No practical alternative design is financially feasible.

The site is adjacent to the newly constructed 23rd Street "Safe Street" pedestrian walkway which connects the University with Rio Grande Street. This street has a double row of trees and a 20 ft sidewalk on the south side of the street and a row of trees on the north side of the street with pedestrian lighting, and street furniture. It is designed to be a major pedestrian route for students to the campus without conflicts with cars.

When redeveloped, this site will have the enhanced streetscape on the Nueces Street frontage conforming to the UNO design requirement of 5inch in diameter class one trees 22 ft on center. These ROW improvements will be installed and maintained under a License Agreement with the City. In this instance, the heritage tree ordinance is in conflict with the Urban Design requirements and the adopted Neighborhood Plan Ordinance set forth for the UNO district.

The University Cooperative Society Inc. respectfully requests the commissions consent to remove tree # 6535.

Sincerely,


Mike McHone, Authorized agent

200 0 XCAUATE TOPROPERT LINE - FOR 7-3 LEVEL A TOPOGRAPHIC AND TREE SURVEY OF 0.583 ACRES, BEING ALL OF LOTS 13, 14 AND 15, SUBDIVISION OF LOUIS HORST'S OUTLOTS IN DIVISION D AND DIVISION E, A SUBDIVISION IN THE CITY OF AUSTIN, TEXAS, OF RECORD IN BOOK Z, PAGE 613 OF THE PLAT RECORDS OF TRAVES COUNTY, TEXAS. BELOW GRADE PARTURE (NT ROK) LEGISIO WK LOCATION CALCULATED POINT MATER VALVE FRE HYDRANT UTILITY POLE ONDREAD UNIONES AZCING UILITY SUBSLLY TOLEPHONE UTILITY MATERIA ER MANHOLE WASSEMARK CLEANOUT (1907) 120.F DOLLARD E15 COCK OF PANEARITY () RECORD COURSES SURVEYOR'S CERTIFICATE: IREE 1857 DATE OF SURVEY: 7/15/95 West 5 7-20-05 7/20/05 Professional Land Surveying, Inc. Surveying and Mapping 2807 Moncheon Rd., Build Austin, Tenes 78704 512-443-1724 SHEET

OWNER'S AUTHORIZATION LETTER I/we hereby certify that I/we am/are the owner(s) of the property reference.

I/we hereby certify that I/we am/are the owner(s) of the property referenced below. I/we am/are respectfully requesting processing and approval of the below referenced permit(s) review. I/we hereby authorize the Applicant listed on this application to act on my/our behalf during the processing and presentation of this request. They shall be the principal contact with the City in processing this application.

Date
Date
2 nd Owner's Printed Name



Bartlett Tree Experts

Tree Inspection Report

Pecan Tree at 507 West 23rd Street in Austin, Texas

Submitted to
George Mitcheil
University Co-op Society, Inc.
507 W. 23rd Street
Austin TX 78713

Submitted by
Steve Kinsiow, Arborist Representative
ISA Certified Arborist #TX-3634A
Bartlett Tree Experts
2403 Howard Lane
Austin TX 78728
512-310-7545



TABLE OF CONTENTS

SUBJECT TREE	1
SITE	
INSPECTION DATES	
ASSIGNMENT	
Summary of Visit Activities	1
INSPECTION METHODS	1
INVESTIGATIONS AND FINDINGS	2
Findings from Visual Inspection	2
Findings from the Sound-Wave Investigation	2
Root Collar Investigation	2
Climbing Inspection	2
DISCUSSION	3
CONCLUSION & RECOMMENDATION	3
TREE RISK STATEMENT	3
PHOTO DOCUMENTATION	1

Tree Inspection Report

Pecan Tree at 507 West 23rd Street in Austin, Texas

SUBJECT TREE

32-Inch Pecan Tree located on the south side of the Co-op facility

SITE

The University Co-op at 507 West 23rd Street, Austin, Texas 78713

INSPECTION DATES

December 6, 2012 December 12, 2012 December 18, 2012

ASSIGNMENT

Perform a visual inspection from the ground and a climbing inspection of the subject tree to observe its general health and structural condition and perform the following additional investigations for more specific information:

- a root collar excavation to approximately eight inches to examine more area of the buttress roots for any defects that might be visible, and
- sound-wave imaging (using the ArborSonic 3-D Acoustic Tomograph) at two locations on the trunk to determine internal indications of decay.

Upon determining findings of these inspections, render a conclusion about the condition of the subject tree and make any related recommendations.

Summary of Visit Activities

On December 6, 2012, 1 met on site with Tammy Migl of Baker-Aicklen & Associates, 1nc., and George Mitchell with the University Co-op. We discussed the tree's condition in light of future development activities being considered for the site. 1 then proceeded to conduct my visual inspection. Based on my findings, Mr. Mitchell approved my returning to conduct the climbing, sound-wave, and root collar inspections. On December 12, 2012, we returned to perform the sound-wave and root collar work. On December 18, 2012, we returned to conduct the climbing inspection to investigate some additional wounds.

INSPECTION METHODS

In addition to visual and climbing inspections, in which we look for specific health and structural indicators, our investigation methods included excavation and sound-wave examination. To perform the excavations, we used a compressed-air tool (an Airspade) that avoids damage to any roots, underground utilities, or similar features. We used a sonic tomography unit to perform the sound-wave examinations on the stem. An explanation of this instrument follows:



ArborSonic 3D Acoustic Tomograph

The Arborsonic 3D Acoustic Tomograph uses sound waves to investigate a tree's internal condition. Typically, a visual inspection reveals external evidence that provides a basis for the examination. The arborist installs a series of sensors around the tree, just through the bark in contact with the sapwood, and taps on one of them, activating the sound waves that travel to the other sensors. The software calculates the sonic velocity, which is correlated to wood density. The resulting color image provides a visual representation of how the sound waves move through the tree, which is an indication of wood density. The accompanying software compares these readings to the known density characteristics of the species and indicates where the tree is less dense than the baseline—an indication of decay.

01/1/6

INVESTIGATIONS AND FINDINGS

Findings from Visual Inspection

My initial observation was that the subject tree was sound-looking. The tree architecture was desirable with good balance and structure. Although the leaves had fallen due to the season, the crown area appeared healthy, with little dead wood apparent. Many pecans were still visible in the crown. At about six feet above grade, a wound was visible on the stem where a branch had been previously removed. Some decay was present in this area (Figure 1). The tree's root flare was visible.

Findings from the Sound-Wave Investigation

We performed sound-wave readings at approximately 16 inches above grade and 63 inches above grade. The higher reading was located just below the stem wound described above. This would provide a better indication of internal decay that might be present in the stem, including toward the tree base, a location more vulnerable to failure risk. The results revealed zero percent decay at the lower location (Figure 2) and one percent decay at the upper location (Figure 3).

Root Collar Investigation

Using the compressed-air tool, we excavated the root collar to about eight inches to expose more area of the buttress roots. No defects were visible based on this examination (Figures 4 and 5).

Climbing Inspection

This inspection revealed three wounds. One appeared on the western most scaffold branch, whose size was approximately 12 inches in length and three inches in depth (Figure 6). The diameter of this branch is 12 inches, and the tree appears to have effectively compartmentalized this wound because sufficient sound wood appears present in the vicinity of the wound.

The second wound is located on the eastern most scaffold branch and was caused by a previous branch failure (Figure 7). No cavity or decay is visible on the wound.

The third wound is located on the south side of the stem (Figure 8). It is a vertical cavity approximately six inches deep, very shallow in relation to the stem diameter.

C/o/Jo

DISCUSSION

Wounding in trees is common. Wounds occur from pruning cuts, failures from storm damage and heavy branch ends, mechanical damage, and other reasons. Whether these are significantly harmful to trees depends on a variety of factors such as wound number and severity; tree species, age, and vigor; and the tree's ability to compartmentalize the wound. When a tree becomes wounded, it doesn't heal; it attempts to wall off the wound by producing chemical and physical boundaries that act to limit the spread of disease and decay organisms. This process, called compartmentalization, is often very successful, and new, healthy wood will form around the wound to strengthen that area over time. The subject tree appears to have effectively compartmentalized the wounds that we observed.

Regarding the sound-wave images, the results indicated near-complete absence of decay. This suggests that the wound directly above the upper reading is effectively walling off movement of decay, especially in a vertical direction, downward. The absence of decay at the lower reading, combined with the good appearance of the buttress roots, suggests that the tree has good strength at a critical area - where the stem and support roots connect.

CONCLUSION & RECOMMENDATION

Our inspections show the subject tree to be healthy with good structure and enough vigor to resist the impacts of wounding. To err on the side of caution, I do recommend that the western most scaffold branch have weight-reduction pruning to reduce risk of failure, given the wound that we observed on this limb.

TREE RISK STATEMENT

Trees inherently pose a certain degree of hazard and risk from breakage, failure or other causes and conditions. Recommendations that are made are intended to minimize or reduce such hazardous conditions. However, there can be no guarantee that efforts to discover or correct unsafe conditions will prevent future breakage or failure, nor can there be any guarantee that all hazardous conditions have been detected. The client should not infer that a tree is safe either because work has been done to reduce risk, or because no work has been recommended on a specific tree.

¹ From the definition of compartmentalization provided by the International Society of Arboriculture.

PHOTO DOCUMENTATION





FIGURE 1: STEM WOUND AT APPROXIMATELY SIX FEET ABOVE GRADE





FIGURE 2: SONIC TOMOGRAPH AT 16 INCHES ABOVE GRADE SHOWING ZERO PERCENT DECAY

Color key: Green = intact, Red = Decayed, Blue = Hollow



C/0/8

FIGURE 3: SONIC TOMOGRAPH AT 63 INCHES ABOVE GRADE SHOWING ONE PERCENT DECAY



FIGURE 4: EXCAVATED ROOT COLLAR



0%

FIGURE 5: EXCAVATED ROOT COLLAR, OPPOSITE VIEW




FIGURE 6: WOUND ON WESTERN MOST SCAFFOLD BRANCH






FIGURE 6: PREVIOUS FAILURE ON EASTERN MOST SCAFFOLD BRANCH




FIGURE 7: SMALL CAVITY ON SOUTH SIDE OF STEM





2-25-13

To: Michael McHone

Fr: Jon Hillis

RE: Pecan Tree Transplant at 507 W. 23rd

Mr. McHone,

Per our conversation this morning, the transplanting of the Pecan tree onsite approximately 100 feet to the southwest of its current location would cost approximately \$146,000 including tax. EDI will provide all labor and equipment necessary to perform the relocation of the subject tree.

Scope:

Preparation: root pruning, airspading, fertilization, canopy pruning, temporary irrigation, monitoring. Rootball encapsulation and piping platform insertion.

Hoisting and conveyance / transport to final location and temporary watering system relocation.

Exclusions: Rock excavation, spoils haul off, spoils infill / compaction, utility re-routes or interference, traffic control, ROW management, replacement of hard surfaces, irrigation source within 100 feet, aftercare / monitoring post-transplant.

This is a brief summary of the site-specific job. There should be more investigation and discourse about the client's needs and space requirements onsite for the construction project. Please call me to discuss or let me know when you would like a full proposal on the relocation of the tree.

Regards,

Jon Hillis

EDI- GM Central Division ISA Certified Arborist: TX-3856A 512-801-6810

SECTION 12 – UNIVERSITY NEIGHBORHOOD OVERLAY (UNO) ZONING DISTRICT DESIGN REGULATIONS

12.1.0 UNIVERSITY NEIGHBORHOOD OVERLAY (UNO) DISTRICT

As governed by Ordinance # 20080925-039, with the goal of promoting high-density and pedestrian-friendly redevelopment in the area generally west of the University of Texas campus, while protecting the single-family residential neighborhoods adjacent to the district.

12.1.1 Purpose *

To establish design criteria for all buildings and streetscapes within the UNO District, including parking structures. The goal is to reinforce the human scale/pedestrian friendly environment of the district. The guidelines discourage the design of monotonous, uninterrupted walls and/or roof planes, and provide the basis for creating active sidewalks through the introduction of street furnishings, street trees and other urban design elements.

12.1.2 Building Design Standards

Buildings, including enclosed and unenclosed parking garages, shall avoid long expanses of blank, unarticulated exterior walls visible from a street, public plaza or public open space. The direction given here regarding massing and articulation of a building's public exterior is considered a matter of human comfort, achievable in any architectural style or design approach.

For a project to be in compliance with the design guidelines, it must score a minimum of 8 points using the following point system:

- a. interruptions in the plane of a building façade shall be introduced at a spacing not to exceed 40-feet. This can be achieved through the articulation of wall surfaces, changes in fenestration patterns, or other building design elements. (2 points)
 - b. use of contrasting materials, textures and colors, (2 points)
- c. introduction of windows and openings that promote visual and physical interaction between interior of building and street activity (2 points),
 - d. the use of awnings or colonnades at street level, (1 point)
 - e. variety of the roof line, (1 point)
- f. articulation of building entrances so they are distinguished from the general massing of the building, (1 point)

g. the use of functional elements such as balconies or projected window boxes to promote the breakdown of a façade. (1 points)

12.1.3 Placement of Windows

- a) inhabited spaces on the ground level shall have a minimum of 70% glass at sides facing a street; where inhabited spaces at ground level hold residential uses, the minimum glass percentage shall be reduced to 40%.
 - b) inhabited spaces on the second level shall have a minimum of 40% glass at sides facing a street.
 - c) glass at ground/street level and second level must have a transmittance ratio of 0.6 or higher.

12.1.4 Building Materials

- a) the use of EIFS below a height of 65 feet is not allowed.
- b) the use of highly reflective glass is not allowed.
- c) wood shingles and wood siding are not allowed.
- d) the use of exposed concrete block as a finish material is not allowed. This includes split-faced, ground face and integrally colored flat concrete block.

12.1.5 Parking Garages – Flat Slab Requirement

Where adjacent to a public street, the floors of a structured parking garage, either stand-alone or mixed into the mass of a building, must either be flat or, if sloping, be hidden from view from the street(s), public plaza or public open space.

12.1.6 Historical Authenticity

Buildings located adjacent to a historic landmark shall create some accommodating element in their massing which will mitigate the contrast between the two.

12.1.7 Streetscape Design Standards

Includes standards for placement of street trees, light poles and street furnishings.

I. STREET TREES:

An owner shall install, irrigate and maintain street trees along an adjacent street right-of-way.

a) all new trees shall be shade trees (non-utility compatible), unless conflict with utilities exist; see I (f). Refer to the Environmental Criteria Manual (ECM) Appendix 'F', for approved street trees species.

- b) street trees must be in scale with adjacent buildings and must be placed so as to create a continuous canopy at maturity.
- c) trees shall have a minimum of 5-inch caliper (measured 12 inches above the root ball) at installation, with a typical canopy height of 14 to 16 feet for Class I Shade trees. Minimum clearance for tree limbs and branches must be 7'-6" above the level of the sidewalk to avoid potential conflict with pedestrians. Trees shall be trimmed proportionally to an ultimate clearance height of 14'-0" above the sidewalk and street at maturity.
 - d) trees shall be installed 4'- 0" O.C. back from face of curb, parallel to the curb.
- e) the standard tree spacing is 22'-0" O.C. If existing conditions preclude the standard spacing, shade trees may be planted at a distance not to exceed 30'-0" O.C.; utility compatible trees spacing shall not exceed 24'-0" O.C.
 - f) where existing utilities are in conflict with in-ground planting of shade trees, applicant shall:
- plant utility compatible trees in above grade planters if both overhead and underground utilities are in place;
 - plant utility compatible trees in-ground, if conflict is with overhead lines;
 - plant shade trees in above grade planters, if conflict is with underground utilities.
- g) a minimum pedestrian clear zone width of 5 feet will be provided between the edge of a tree grate/planting bed and any walls/planters and/or other vertical element associated with a development (refer to COA Detail 710S-6A). If above grade planters are used, the minimum pedestrian clear zone shall be 6 feet (as per COA Detail 432S-7D).
- h) a new tree planted in a sidewalk must have a 6 feet x 6 feet tree grating which shall comply with COA Standard Detail 437S-2. A different plant bed configuration with or without a tree grate, may be approved by the Planning and Development Review Department, based on specific needs and an alternative form of equivalent compliance.

II. PEDESTRIAN SCALE STREET LIGHTING:

All development shall provide pedestrian scale street lighting along an adjacent street right-of-way.

- a) the standard pedestrian scale street light pole spacing is 44'-0" O.C.; lights may be placed as far apart as 72'-0" O.C. if existing conditions preclude the recommended spacing.
- b) on corner properties, the distance between the corner and the first light pole shall not exceed 25'-0".
 - c) light poles shall be installed 4'-0" O.C. back from face of curb, aligned with the street trees.
 - d) A minimum spacing of 11'-0" O.C. shall be maintain between a light pole and a street tree.
 - e) the "Pecan Street Light Pole" is the University Neighborhood Overlay fixture.

III. STREET FURNISHINGS:

Street furnishings, including benches, bike racks and trash receptacles, shall be provided by any development located within the Dobie, Guadalupe and Inner West Campus Sub-districts.

In the Outer West Campus Sub-district, only developments with greater than 150 linear feet of cumulative street frontage shall be required to provide street furnishings described here.

Within a given project, the street furnishings will compliment each other and the development they are a part of.

Permitted finishes shall be one or a combination of the following: decay resistant hardwoods (benches slats only), and corrosion resistant finishes such as aluminum, cast iron, stainless steel or galvanized steel.

Whenever applicable, street furnishings will be anchored with rust-resistant fasteners and treated with rust prohibitive coating, zinc epoxy primer, and powdercoat finish for superior corrosion resistance. All surfaces shall be pretreated with a grafitti preventer.

The street furnishing requirements are as follows:

- a) Trash Receptacles: A minimum of one (1) receptacle shall be provided:
- For mid-block properties, the receptacle shall be located within 12 feet of a primary entrance(s), aligned with lights and trees.
- For corner properties, two (2) additional receptacles shall be provided adjacent to the corner ramps, facing both streets, (as per COA Standard Detail 432S-8C).
- b) Bike Racks: A minimum of four (4) bike racks, in addition to those required in other sections of the code.
- Bike racks shall be installed perpendicular to the curb, 4'-0" O.C. back from face of curb, aligned with trees and light poles (as per COA Standard Detail 710S-6A).
- Bike racks shall be Class III, Type 1 inverted "U"(1-2 spaces only) as per COA Standard Detail 710-S-1 (page 1 of 3).
- Racks shall be made of continuous welds, with smooth edges. Finishes shall be one of the following: cast aluminum, stainless or galvanized steel or plastic color coated carbon steel.
 - Stainless steel tubing shall be 1 ½ inch,
- When applicable, a fade resistant powder coat finish color shall use RAL color standards for compatibility with other products.
- c) Benches: A minimum of two (2) 5-foot wide benches with middle arm shall be installed per street frontage:
 - Standard placement: perpendicular to the curb and aligned with the trees and light poles,

and facing each other arranged in a conversational grouping (as per COA Standard Detail 432S.


- If existing conditions preclude the standard placement benches may be placed parallel to the building, facing the street, within 6 inches of the building exterior wall (as per COA Standard Detail 432S),
 - Finishes may be metal or a combination of metal frame with wood slats.
- Only hardwoods that are responsibly produced, durable and resistant to fire, moisture, insects, decay or vandalism i.e. Redwoods, shall be used. Stained, painted or varnished wood shall not be allowed.
- If a corner property, two (2) benches will be installed along each street frontage for a total of four (4) benches minimum.

Disclaimer:

This Code of Ordinances and/or any other documents that appear on this site may not reflect the most current legislation adopted by the Municipality. American Legal Publishing Corporation provides these documents for informational purposes only. These documents should not be relied upon as the definitive authority for local legislation. Additionally, the formatting and pagination of the posted documents varies from the formatting and pagination of the official copy. The official printed copy of a Code of Ordinances should be consulted prior to any action being taken

For further information regarding the official version of any of this Code of Ordinances or other documents posted on this site, please contact the Municipality directly or contact American Legal Publishing toll-free at 800-445-5588.

> © 2008 American Legal Publishing Corporation techsupport@amlegal.com 1.800.445.5588.



Proposed Changes in Height

Mike McHone Real Estate



Keith Mars
City of Austin
505 Barton Springs Rd.
Austin, Texas 78704

February 22, 2013

Re: Heritage Tree Review Application/ Environmental Board Review March 6, 2013

Mr. Mars:


Attached is supplemental information for this application.


- 1. Site Plan indicating the full 3 lots of the site and the location of the subject tree (# 6535)
- 2. Three pages of the site plan of 21 Rio a similarly located UNO project at 21° Rio Grande
 - a. Elevation showing massing and step back at 65 ft of height (this project is on a site that is 120ft by 140 ft.
 - b. Elevation showing common wall along adjacent property
 - c. Site plan showing 100% building coverage, and adjacent streetscape
- 3. Aerial view of site showing the adjacent construction
- 4. Street view of the northeast corner of the site from the alley looking southwest
- 5. Street view look east from Nueces midway on the site
 - a. Heritage tree to right of frame
 - b. Large pecan in ROW
 - c. Power pole in foreground

This should help the Board get a better context of the challenges in dealing with this tree and conforming to the UNO requirements.

Respectfully.

Mike McHone







Google earth

feet 400 neters 100

EXISTING CONDITION SHOWING
23tel Steet PEDESTAIN WALKWAY





Google earth

feet 10 meters

VIEW FROM 23 SCROT AT ALLEY LOOKING & W.

21 RIO IN DISTANT BALK GRAND

SUBJECT THEE IN MIDDLE

UTILITY LINES IN ALLEY

PEPESTRIAN STREETS BAPE ON SOUTH SIDE OF 23 2 SLADY.



Google earth feet 10 meters

Subject TREE TO LEGT - PARKING LOTS PART OF SITE
LOOKING ENCY FROM NOW STREET
Power Pole + TREE , U ROW